



**(43) International Publication Date**  
**17 February 2005 (17.02.2005)**

PCT

(10) International Publication Number  
**WO 2005/015795 A1**


- (51) **International Patent Classification<sup>7</sup>:** **H04J 3/08** (74) **Agents:** **BATTIPEDE, Francesco** et al.; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milano (IT).
- (21) **International Application Number:** PCT/EP2003/008633 (81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) **International Filing Date:** 5 August 2003 (05.08.2003)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (71) **Applicant (for all designated States except US):** **TELECOM ITALIA S.P.A.** [IT/IT]; Pizza degli Affari, 2, I-20123 Milano (IT).
- (84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** **ALLASIA, Andrea** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). **RITA, Roberto** [IT/IT]; Via di Val Cannuta, 250, I-00100 Roma (IT). **SERRA, Laura** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). **VARETTO, Luigi, Giuseppe** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT).
- Declarations under Rule 4.17:**
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES,

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES,

*{Continued on next page}*

- (54) Title:** METHOD FOR PROVIDING EXTRA-Traffic Paths With Connection Protection In A COMMUNICATION NETWORK, RELATED NETWORK AND COMPUTER PROGRAM PRODUCT THEREFOR



- (57) **Abstract:** Extra traffic (ET) paths are provided in a communication network including at least two protection channels associated to respective transmission channels. Each protection channel admits: - an active state for carrying, in the presence of a failure in said associated transmission channel, traffic to be carried by the associated transmission channel, and - a stand-by state, wherein the protection channel is adapted to carry extra traffic. The protection channels are run in a sub-network connection protection scheme, whereby one of the protection channels in its stand-by state is adapted to ensure recovery of extra traffic carried by the other protection channel while the other protection channel is switched to its active state or is subject to failure.

WO 2005/015795 A1



FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

"Method for providing extra-traffic paths with connection protection in a communication network, related network and computer program product therefor"

5

\* \* \*

Field of the invention

The invention relates to telecommunication networks and was developed by paying specific attention to the possible application to ring architectures in  
10 SDH (Synchronous Digital Hierarchy) networks of the type currently designated MS-SPRing.

Reference to this possible field of application is not however to be construed as limiting the scope of the invention.

15

Description of the related art

Long distance transmission networks provide a wide variety of different telecommunication services, such as voice and Internet data or leased lines at different speeds.

20

These networks generally include a plurality of nodes, each typically located in a city or other high traffic location, coupled together in a closed loop or a ring/mesh architecture e.g. by fiber optic cables. The information travels over the fiber according to  
25 optical transmission standards such as e.g. those currently referred to as Synchronous Digital Hierarchy (SDH) or Synchronous Optical Network (SONET).

In ring architectures, traffic protection can be easily performed creating two separate links over the  
30 loop and dedicating the former to normal flow and the latter to protection, in order to ensure service when a fault event occurs in the former link.

This protection arrangement is currently designated sub-network connection protection (SNCP). In  
35 this kind of protection arrangement no specific mechanisms exist for coordinating both ends of the

link. This means that no specific protocol exists for exchanging information between protection terminations about "switch" and "bridge" (e.g. protection) states.

One possible implementation of a sub network connection protection scheme involves two equipments that carry traffic along a certain infrastructure (e.g. a ring). The network element at the source end of the protection span transmits the protected channel over the two sides of the ring as a protection group. The network element at the sink end of the protection span outputs the received protection group as a choice of the "best" sides depending by switching criteria. In case no defects are detected in the working SNC/trail signals, these signals are selected as the normal signals. The SNCs/trails selected by the sink end are called the active SNCs/trails, while the others are called the standby SNCs/trails.

Trail protection schemes exist (such as the scheme designated Multiplex Section Protection or MSP) that offer the possibility of using an in band protocol in order to synchronize both terminations. This feature may be exploited to establish channels adapted to be routed via the protection trail/section/path in standby condition. The signals conveyed over such channels are usually called extra traffic (ET), see e.g. ETSI EN 300 417-1-1, v1.2.1, (2001/10), "Transmission multiplexing; generic requirements of transport functionality of equipment; Part1-1: generic process and performance; page.18.

A so-called MS-SPRing protection scheme can be implemented by means of a two or four fiber Multiplex Section Shared Protection Ring (MS-SPRing). On each span, half of the capacity (with one or two couples of fibers) is dedicated to "working" channels and the other half to "protection" channels. Traffic can flow over the ring in a clockwise or counter-clockwise

direction. In case of a single fiber failure, a span protection scheme is applied, and traffic is re-routed along the protection span adjacent to the failed one. In case of second order faults (e.g. working and protection fiber failures or node failure) a ring protection scheme is implemented and traffic is re-routed along the non-failed side of the ring.

Figure 1, including four portions designated a) to d) respectively, schematically represents the operation of a typical MS-SPRing protection scheme involving four nodes designated a, n1, n2, and Z.

In figure 1, "working" and "protection" fibers are shown, the protection fibers being represented by hashed areas and failure events by crosses.

Specifically, in figure 1 the four following conditions are shown:

- (a) normal operation;
  - (b) span protection active;
  - (c) ring protection against double span failure
- and;
- (d) ring protection against node isolation

In addition to the normal MS-SPRing protection algorithm (which offers protected channels with high priority levels), the possibility exists of exploiting non-preemptible unprotected traffic (NUT) channels to offer an intermediate priority level and extra traffic (ET) channels having low priority levels.

In particular, some working and protection channels in a MS-SPRing arrangement can be used to carry NUT, which is unprotected traffic traveling on specific channels on working and protection paths of the ring. In case of failure, these channels cannot be cut off to support protection of normal traffic.

In bi-directional protection schemes, where a termination coordination protocol is available, the band normally reserved to protection can be exploited

to carry extra traffic when the protection channel is in standby mode. Obviously, when a failure event occurs on the working path, and the protection scheme switches from the working to the protection path, the extra traffic channel is pre-empted and its recovery is not guaranteed.

As shown in figure 2, a 1+1 protection architecture has one normal traffic signal, one working SNC/trail, one protection SNC/trail and a permanent bridge.

A m:n protection architecture has n normal traffic signals, n working SNCs/trails and m protection SNCs/trails. The signals on the working SNCs/trails are the normal traffic signals. The signal on a protection SNC/trail is either one of the normal traffic signals, an extra traffic signal, or a null signal. At the source end, any of the signals mentioned can be connected to the protection SNCs/trails. At the sink end, the signals from the working SNCs/trails are selected as the normal traffic signals. In case of a defect condition on a working SNC/trail, the transported signal is routed over one of the protection SNCs/trails. At the sink end, the signal from this protection SNC/trail is then selected instead.

The recommendation ITU-T G.841 "Series G: Transmission systems and media, digital systems and network - Types and characteristics of SDH network protection architectures", Oct. 1998, indicates that a further differentiation on priority levels may be achieved by considering a sub network connection protection mechanism partially embedded in a MS-SPRing using NUT. In other words, NUT may be protected along the MS-SPRing with the implementation of a SNCP path. This kind of protection preserves NUT from double failures over a span.

NUT channels are however affected by two main

disadvantages, namely:

- for using a NUT channel, it is necessary to create more paths than needed; for example, for a NUT channel on the working bandwidth, it is necessary to dedicate it the slot number one of all the working and protection spans forming the ring;
- for creating a non-planned link in a NUT configuration, it is necessary to perform a ring re-commissioning.

10 In WO-A-02/073903 an arrangement is disclosed for achieving an availability differentiation through the definition of a different technology also known as resilient packet ring (RPR) technology. In this arrangement, different availability levels are obtained  
15 by defining three classes of service each one having a different priority level. The three classes of traffic are the following: protected traffic (i.e. high priority); unprotected traffic (i.e. medium priority); and emplaceable traffic (i.e. low priority).

20 The main disadvantage of this solution is that operators wishing to develop network facilities to deploy different levels of service will be inevitably forced to change equipment with a great impact on the capital expenses.

25 Document WO-A-01/030006 describes a variant of the SNCP protection scheme discussed in the foregoing providing another implementation of a 1+1 protection scheme. Specifically, the possibility of carrying unprotected and un-rerouted extra traffic signals on the  
30 protection path of a 1+1 sub network connection protection scheme is suggested, when the protection trail is in a stand-by condition.

#### Object and summary of the invention

The need therefore exists for improved  
35 arrangements that may be adapted to create paths with different availability levels by dispensing with the

disadvantages intrinsic in the prior art arrangement discussed in the foregoing.

The object of the present invention is thus to provide such an improved arrangement.

5 According to the invention, such an object is achieved by means of method having the features set forth in the claims that follow. The invention relates to corresponding system, as well as a corresponding computer program product loadable in the memory of at  
10 least one computer and comprising software code portions for performing the steps of the method of invention when the product is run on at least one computer. Reference to "at least one" computer is intended to highlight the possibility for the  
15 arrangement of the invention to be carried out in a decentralized manner.

A preferred embodiment of the invention is based on an improved way to protect extra traffic (ET) channels, by exploiting a sub network connection  
20 protection scheme applied to the MS-SPRing architecture.

Protection is based on the principles underlying the functional model of ITU-T Recommendation G.803.

As used herein, the intended meaning of "sub  
25 network connection protection" is not limited to the specific arrangement currently identified by the acronym SNCP, but also extends to equivalent protection schemes such as e.g. those known as MS-SPRing, Restoration and Multi Protocol Label Switching (MPLS)  
30 or Generalized MPLS.

Such a protection scheme preferably makes use of pre-assigned capacity between nodes. The simplest architecture has 1 working and 1 protection capacity (1+1), the most complex architecture has n working  
35 capacities and m protection capacities (m:n), respectively.



The arrangement described herein offers the possibility of creating a path protected service using two low priority extra traffic (ET) channels present in a four-fiber MS-SPRing arrangement. Extra traffic  
5 channels may be protected in a MS-SPRing structure by doubling an extra traffic channel along the clockwise and counter-clockwise sides of the ring and applying a sub network connection protection protocol.

This strategy of protection offers an opportunity  
10 for further differentiating the service priority levels. In fact, sub network connection protection on extra traffic channels allows recovery of such a low priority traffic in case of a single failure along any span of the ring. As a consequence, a new intermediate  
15 level of protection is achieved among the levels assured by NUT and SNCP protected NUT.

As indicated, NUT channels have two main disadvantages, namely:

- for using a NUT channel, it is necessary to  
20 reserve more bandwidth than needed; for example, for a NUT channel on the working bandwidth, the slot "number one" slot of all the working and protection spans forming the ring must be dedicated to it; and
- in order to create a non-planned link in NUT  
25 configuration, it is necessary to perform a ring re-commissioning.

Referring to the disadvantages of NUT channels described in the previous section, extra traffic does not permanently reserve a channel along the protection  
30 path.

The arrangement described herein is technology independent. This means that only two basic requirements for the network protocol of transmission exist, namely:

- 35 - having a form of circuit protection; and
- having the possibility of configuring low

priority traffic with respect to the normally protected one.

The matching between low priority path and sub network connection protection capabilities can be achieved either on the same network equipment or on a different equipment. In other words, almost all the network equipments having low priority traffic capabilities are adapted to use the combination with SNCP protection.

By way of direct comparison, while the arrangement shown in WO-A-01/030006 discloses the possibility of carrying extra traffic over a 1+1 SNCP protection scheme (which i.a. is not described in normative documents), in the arrangement described herein the protection path of a MS-SPRing scheme is exploited to carry extra traffic signals and a method to protect ET by a 1+1 SNCP implementation scheme is shown.

A preferred embodiment of the arrangement disclosed herein thus provides extra traffic paths in a communication network including at least two protection channels associated to respective transmission channels.

Each protection channel admits:

- an active state for carrying, in the presence of a failure in said associated transmission channel, traffic to be carried by the associated transmission channel, and

- a stand-by state, wherein the protection channel is adapted to carry extra traffic.

The protection channels are run in a sub-network connection protection scheme, whereby one of the protection channels in its stand-by state is adapted to ensure recovery of extra traffic carried by the other protection channel while the other protection channel is switched to its active state or is subject to failure.

Preferred embodiments of the arrangement disclosed herein provide:

- at least one ring structure including non-coextensive paths and associating the at least two protection channels to respective non-coextensive paths in the ring (i.e. by resorting to what is currently designated "routing diversity", and
- a plurality of ring structures and associating the at least two protection channels to respective, different rings of the plurality of rings.

#### Brief description of the drawings

The invention will now be described, by way of example only, by referring to the enclosed figures of drawing, wherein:

- figures 1 and 2, related to the prior art, has been described previously,
- figure 3 shows an SNCP protected path through two extra traffic channels between two different nodes,
- figure 4 shows a ring arrangement implementing a four fiber MS-SPRing protection scheme,
- figures 5 and 6 show two possible failure events occurring in the arrangement of figure 4,
- figure 7 shows two extra traffic channels protected with a sub network connection protection scheme,
- figure 8 shows an alternative arrangement to the arrangement of figure 7,
- figures 9 and 10 show various arrangements for routing differentiation over two rings,
- figures 11, 12 and 13 show various configurations for availability/unavailability evaluation,
- figure 14 is a general representation of extra traffic protected via a sub network connection protection scheme.

#### Detailed description of preferred embodiment of

the invention

Figure 3 of the drawing is a representation of a SNCP protected path between two equipments 10 and 12.

A backbone network based on a ring interconnected  
5 architecture with four fibers MS-SPRing protection can offer a wide network service portfolio based on different levels of availability. The arrangement described herein enlarges the possibilities of service level differentiation on a MS-SPRing SDH network.

10 This arrangement is essentially the application of the SNCP protection scheme to extra traffic channels A, B in a network N extending between two equipments 10 and 12. The two extra traffic channels A and B are sent along the working and protection trails of a SNCP  
15 protection architecture. Specifically, figure 4 shows a SNCP protected path including two extra traffic channels between two different nodes 10 and 12.

Figure 4 shows a four fiber MS-SPRing protection scheme architecture, with extra traffic on the  
20 bandwidth of the protection sections. Specifically, figure 4 (and figures 5 to 8 as well) refer to a ring arrangement provided between two nodes 100, 200 including respective data exchange control (DXC) modules and including four add-drop multiplexers ADM1  
25 to ADM4. Two extra traffic channels are depicted, routed on the two opposite sides of the ring.

In the ring with four fiber MS-SPRing protection scheme, the bandwidth of the protection paths may be dedicated to extra traffic as shown with two extra  
30 traffic channels, on the two opposite sides of the ring. The paths terminate on two digital cross connects.

Figure 5 shows interruption of channel number 1 when a span failure occurs, with channel number 2  
35 working normally and the state of the two extra traffic channels in case of span protection: path number 1 is

out because the protection path is devoted to normal traffic span protection, while path number 2 is regularly in service.

Figure 6 shows interruption of channels number 1 and number 2 when a double span failure occurs. The ring works in ring protection mode in which both extra traffic paths have been emptied to allow the re-routing of high priority traffic.

Service level agreement currently require that, when this faulty condition occurs, ring fibers and/or equipments must be repaired in a few hours (typically less then one work day).

As already mentioned in the foregoing, referring to NUT channels, a further differentiation on priority levels may be achieved by a composite solution, using NUT channels in a four fiber MS-SPRing with an overlaid sub network connection protection scheme. In other words, NUT may be protected along the MS-SPRing with the implementation of a sub network connection protection path. This kind of protection preserves NUT from double failures along a span.

The different solutions analyzed so far are not exempt from certain critical aspects.

NUT channels allow both protected and unprotected channels on the same infrastructure but, when a ring is in the commissioning phase, necessitate exactly planning the bandwidth requirements because any difference implies a new re-commissioning phase in order to optimize the reused ring bandwidth.

Sub network connection protection of NUT channels implies that, in the network planning phase, i.e. in the ring commissioning phase, the NUT channels required to carry out traffic demands must be defined. For just one traffic demand it is necessary to define one slot for the whole ring as NUT (this implies that the bandwidth allocated is greater than the one effectively

used).

Using extra traffic channels on a MS-SPRing infrastructure offers an availability level that is much lower in comparison with the protected channels.  
5 In addition, the extra traffic availability is also affected by long outage periods due to planned maintenance activity.

A preferred embodiment of the arrangement described herein offers the possibility of creating a  
10 path protected service using two low priority extra traffic channels present on four-fiber MS-SPRing.

As previously discussed in the case of NUT, extra traffic channels may be protected in a MS-SPRing structure by doubling an extra traffic channel along  
15 the clockwise and counter-clockwise sides of the ring and applying a sub network connection protection protocol.

This protection scheme offers an opportunity to further differentiate the service priority levels. In  
20 fact, sub network connection protection of extra traffic channels allows the recovery of low priority traffic in case of a single failure along any span of the ring.

Availability evaluation shows that the protection  
25 level obtained is higher than in the case of simple NUT channels (this is because the path is protected on the two different routes of the ring) but lower with respect to SNCP protected NUT.

In comparison with the NUT implementation, an  
30 advantage of using extra traffic channels with an sub network connection protection scheme lies in planning the ring capacity for extra traffic services, so a commissioning activity is not required any time an extra traffic channel is to be provisioned.

35 Within this context, at least two embodiments are possible, namely:

- two extra traffic channels protected with a sub network connection protection scheme having the bridge-selector function performed on the same add drop multiplexers (ADMs) forming the ring; and
- 5       - two extra traffic channels protected with an SNCP scheme having the bridge-selector function performed on digital cross connects (i.e. DXCs).

Specifically, figure 7 shows two extra traffic channels protected with a sub network connection  
10 protection scheme having the bridge-selector performed on the same add drop multiplexers (ADMs) forming the ring.

Conversely, figure 8 shows two extra traffic channels protected with a sub network connection  
15 protection scheme having the bridge-selector performed on digital cross connects (DXCs).

In the implementation of the sub network connection protection scheme over the add drop multiplexers (ADMs) forming the ring infrastructure  
20 that carries traffic patterns, a sub-network termination point is created that includes two extra traffic paths routing over the two opposite sides of the ring, as represented in Figure 4.

In the implementation of the sub network connection extra traffic protection scheme over the  
25 DXCs, the equipment represents the path termination, in a specific network domain, of a path created by two extra traffic sub-paths protected via a sub network connection protection scheme. In this latter case,  
30 different possibilities exist for establishing the extra traffic services, that depend on the routing strategy applied to the infrastructure (e.g. routing via minimum number of rings).

Specifically the following situations may arise:

- 35       - in case of extra traffic paths protected via the SNCP algorithm over a single ring, as described above,

the SNCP mechanism can be configured over the ADMs while the ring infrastructure deploys the ET paths in routing diversity (see again figure 7);

- in case of extra traffic paths protected via the sub network connection protection algorithm over the same ring, the sub network connection protection mechanism can be configured over the DXCs as a variant of the previous scheme (see, in that respect, figure 8);

- in case of extra traffic paths protected via SNCP algorithm over different rings, the sub network connection protection mechanism can be configured over the DXC and the ring infrastructure should be represented as extra traffic paths carried over two different rings belonging to the same class (i.e. a ring number "one" and a ring number "two")

Extra traffic paths can also be carried over two rings belonging to different ring classes (i.e. a ring number "one" of class A and a ring number "one" of class B).

In respect of this last mentioned option, it is important to understand that this strategy achieves an improvement in terms of path survivability and, specifically, offers good protection level when a planned maintenance activity affects the operability condition of one of the extra traffic paths used in SNCP protection scheme.

In order to reach the maximum theoretical advantage from extra traffic paths carried out over two different rings of the same class, the working and the protection paths are planned on different routing. If the different routing is represented by two rings that belong to the same class (over the same cable infrastructure are deployed two or more different ring systems, a. A way of obtaining routing diversification is to route one extra traffic path on one side of the



first ring and the second extra traffic on the opposite side of the second ring. This means that only two faults over the same span (working and protection) may lead to an out of service condition.

5 Specifically, figure 9 shows routing differentiation over two rings of the same class, which leads to a significant advantage from the extra traffic protection via a sub network connection protection scheme.

10 In the case of extra traffic paths carried out over two rings belonging to different ring classes, a complete diversification of routing (i.e. different equipments and infrastructures) is possible, so that the availability level reaches its maximum.

15 In that respect, figure 10 shows routing differentiation over two rings of the same class, which leads to a maximum advantage from the extra traffic protection via a sub network connection protection scheme.

20 It will be appreciated that two additional ADMs (namely ADM5 and ADM6) are shown in ring number one of class Y in order to highlight that the ring structures considered herein may include any number of network equipments as provided for in the ITU-T G.841  
25 specification.

The following is a discussion of investigations performed on a ring structure interconnecting two geographical sites (again designated 100 and 200) with two different paths named red (R) and blue (B)  
30 directions.

The unavailability figures of NUT and extra traffic (ET) channels have been calculated in three cases.

In the first case (figure 11), the calculation is  
35 performed on a point-to-point link, along the red (R) or blue (B) paths.

In the second case (figure 12), two NUT or ET channels have been created along the red (R) and blue (B) paths, in order to perform a sub network connection protection scheme (the shortest path has been  
 5 considered as "working" and the longest one as "protection").

In the third case (figure 13) the sub network connection protection scheme is performed on the DXC equipment, thus allowing the infrastructure  
 10 diversification of the working and protection channels (ring 1 and ring 2).

The equipments and infrastructure unavailability values are reported in Table 1 below

15 Table 1

| Network element      | Functional lock     | Unavailability<br>[abs] |
|----------------------|---------------------|-------------------------|
| ADM                  | STM1 ports          | 1.36711E-05             |
|                      | Matrix              | 1.37079E-10             |
|                      | Common parts        | 3.52434E-05             |
|                      | Line ports          | 2.53672E-05             |
| RED                  | STM1 ports          | 4.11369E-06             |
|                      | Matrix              | 1.0824E-09              |
|                      | Common parts        | 1.46034E-05             |
| Ring characteristics | Fibre /km           | 0.000003                |
|                      | Rings circumference | 1000 km                 |
|                      | n. ADM/ring         | 4                       |

20

25

Table 2 summarizes the results obtained in the three cases described above.

Table 2

| Case | Node A          | Node Z | Path     | Protection type            | Unavailability<br>[abs] | Availability<br>[%] | Unav.<br>min/year |
|------|-----------------|--------|----------|----------------------------|-------------------------|---------------------|-------------------|
| 1    | A1              | Z1     | red      | ET                         | 0,008218322             | 99,180              | 4319              |
|      | A2              | Z2     | blue     | ET                         | 0,00900645              | 99,100              | 4733              |
|      | A1 <sup>s</sup> | Z1     | red      | NUT                        | 0,00474275              | 99,526              | 2493              |
|      | A2              | Z2     | blue     | NUT                        | 0,00545401              | 99,455              | 2867              |
| 2    | A               | Z      | ring 1   | ET SNCP ADM                | 0,00011064              | 99,990              | 58                |
|      | A               | Z      | ring 1   | NUT SNCP<br>ADM            | 0,00002587              | 99,997              | 14                |
|      | A               | Z      | ring 1   | MS-SPRing<br>protected ADM | 0.00002055              | 99,998              | 11                |
| 3    | A               | Z      | ring 1-2 | ET SNCP RED                | 0,00013148              | 99,989              | 69                |
|      | A               | Z      | ring 1-2 | NUT SNCP<br>RED            | 0,00004420              | 99,996              | 23                |
|      | A               | Z      | ring 1   | MS-SPRing<br>protected RED | 0.00004175              | 99,996              | 22                |
|      | A               | Z      | ring 2   | MS-SPRing<br>protected RED | 0.00004162              | 99,996              | 22                |

5 The data show NUT channels to have fewer minutes of unavailability when compared to the ET channels. For both types of protection, the order of magnitude ranges from the thousands of minutes in the non-protected case to tens of minutes for the SNCP ones. The  
 10 unavailability of ET channels protected SNCP stands in between the unavailability figures of unprotected and SNCP protected NUT.

The arrangement described herein is adapted for use in meshed architecture networks where ET sub-paths  
 15 use the bandwidth defined for traffic restoration. This is shown, in quite general terms, in figure 14, where

one such network is indicated by the reference number 1000.

The meshed infrastructure shown therein is implemented via digital cross connects interconnected with line terminals. Each branch in the network plan has associated a certain amount of bandwidth to recover equipment or cable failures. When the network efficiency is failure exempt, the band reserved to recovery is unused and can be configured to carry out ET. In order to increase the availability ratio it is possible to protect two channels by an sub network connection protection scheme.

The focus of the arrangement described herein is on the protection of paths realized in low priority configuration. The embodiment described concerns SDH technology with ring or meshed architecture.

In this kind of network, data are transmitted via TDM (Time Division Multiplexing) in those protected channels (i.e. high priority channels) whose length is fixed (VC). Each channel carries one or more circuit data flows defined by the implemented protocol. Networks of this kind include, for example, SDH (Synchronous Digital Hierarchy) or SONET (Synchronous Optical Network) networks.

In this kind of network, with high priority channel, extra traffic channels (i.e. low priority channels) can be configured in various ways.

In WDM (Wavelength Division Multiplexing) networks, data are transmitted on different wavelengths, which replace the multiplexing time slots. With this technology it is possible to create the so called "lambda" protected paths; the lambda (i.e. the wavelength) reserved to the protection of the main lambda, or in sharing with a bundle of other lambdas, can be assigned the role of carrying low priority traffic. From a technical point of view, extra traffic

in SDH and SONET networks and low priority lambdas in WDM networks can be considered equivalent. They are both empty channels when a failure state occurs, regardless of the actual physical implementation of the  
5 network.

Also, SDM (Space Division Multiplexing) or FDM (Frequency Division Multiplexing) networks can be similarly implemented. In these cases the concept of Extra Traffic paths is associated to intervals of space  
10 or frequency. As is well known, FDM was the dominant technology before TDM technology was developed.

The invention refers to all types of networks based on the concept of circuit protection described above. Specifically, reference made in the description  
15 to TDM (SDH and SONET) and WDM networks is primarily dictated by their current popularity.

A restoration application makes use of any capacity available between nodes. In general, restoration will involve re-routing. When restoration  
20 is used, a percentage of the transport network capacity will be reserved for re-routing working traffic. Restoration is initiated (in a known manner) by the network operator and as such does not fall within the scope of the present document.

25 It is thus evident that, the basic principles of the invention remaining the same, the details and embodiments may widely vary with respect to what has been described and illustrated purely by way of example, without departing from the scope of the  
30 presented invention as defined in the annexed claims.

CLAIMS

1. A method of providing extra traffic (ET) paths in a communication network including at least two protection channels (A, B) associated to respective transmission channels, each of said at least two protection channels (A, B) admitting an active state for carrying, in the presence of a failure in said associated transmission channel, traffic to be carried by the associated transmission channel and a stand-by state, wherein the protection channel is adapted to carry extra traffic (ET), characterized in that it includes a step of running said at least two protection channels (ET) in a sub-network connection protection scheme, whereby one of said at least two protection channels (A, B) in said stand-by state is adapted to ensure recovery of extra traffic carried by the other of said at least two protection channels (A, B) while one of the following conditions is met:

- said other of said at least two protection channels (A, B) is switched to said active state,
- said other of said at least two protection channels (A, B) is subject to failure.

2. The method of claim 1, characterized in that it includes the steps of:

- associating to each of said at least two protection channels (A, B) corresponding input and output digital cross connects (DXCs), and
- running said sub-network connection protection scheme at said input and output digital cross connects (DXC).

3. The method of claim 1, characterized in that it includes the steps of:

- associating to each of said at least two protection channels (A, B) corresponding input and output add-drop multiplexers (ADM), and

- running said sub-network connection protection scheme at said input and output add-drop multiplexers (ADM).

4. The method of claim 1, characterized in that it includes the steps of providing in said communication network at least one ring structure including non-coextensive paths and the step of associating said at least two protecting channels (A, B) to respective non-coextensive paths in said ring.

10 5. The method of claim 1, characterized in that it includes the steps of providing in said communication network a plurality of ring structures and the step of associating said at least two protection channels (A, B) to two respective different rings of said plurality  
15 of rings.

6. The method of claim 5, characterized in that in it includes the step of selecting said two different rings as rings belonging to the same class of rings.

7. The method of claim 5, characterized in that in  
20 it includes the step of selecting said two different rings as rings belonging to different classes of rings.

8. The method of claim 1, characterized in that it includes the step of providing a non-preemptible unprotected traffic (NUT) carried on non-preemptible  
25 channels in said network as well as non-preemptible channels protected by a sub-network connection protection (SNCP) scheme, wherein said extra traffic is ensured an intermediate level of availability between the levels of protection provided by said non-  
30 preemptible channels and by said non-preemptible channels protected by a sub-network connection protection (SNCP) scheme.

9. A communication network including at least two protection channels (A, B) associated to respective  
35 transmission channels, each of said at least two protection channels (A, B) admitting an active state

for carrying, in the presence of a failure in said associated transmission channel, traffic to be carried by the associated transmission channel and a stand-by state, wherein the protection channel is adapted to  
5 carry extra traffic (ET), characterized in that said at least two protection channels (ET) jointly define a sub-network connection protection scheme, whereby one of said at least two protection channels (A, B) in said stand-by state is adapted to ensure recovery of extra  
10 traffic carried by the other of said at least two protection channels (A, B) while one of the following conditions is met:

- said other of said at least two protection channels (A, B) is switched to said active state,
- 15 - said other of said at least two protection channels (A, B) is subject to failure.

10. The network of claim 9, characterized in that it includes corresponding input and output digital cross connects (DXCs) associated to each of said at  
20 least two protection channels (A, B) and wherein said input and output digital cross connects (DXC) jointly define said sub-network connection protection scheme.

11. The network of claim 9, characterized in that it includes corresponding input and output add-drop  
25 multiplexers (ADM) associated to each of said at least two protection channels (A, B) and wherein said input and output add-drop multiplexers (ADM) jointly define said sub-network connection protection scheme.

12. The network of claim 9, characterized in that  
30 it includes at least one ring structure including non-coextensive paths and wherein said at least two protecting channels (A, B) are associated to respective non-coextensive paths in said ring.

13. The network of claim 9, characterized in that  
35 it includes a plurality of ring structures and wherein said at least two protection channels (A, B) are



associated to two respective different rings of said plurality of rings.

14. The network of claim 13, characterized in that said two different rings belong to the same class.

5        15. The network of claim 13, characterized in that said two different rings belong to different ring classes.

16. A computer program product loadable in the memory of at least one computer and including software  
10 code portions for performing the steps of the method of any of claims 1 to 8.

Fig. 1




Fig. 2








Fig. 3










Fig. 9




Fig. 10




Fig. 11




Fig. 12





Fig. 13



## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 03/08633

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04J3/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04J H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages   | Relevant to claim No. |
|------------|--|-----------------------|
| Y          | ETSI: "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 1-1: Generic processes and performance" ETSI EN 300 417-1-1 V1.2.1 (2001-10), 'Online! - 12 October 2001 (2001-10-12) pages 1-151, XP002273772 Retrieved from the Internet: <URL:http://webapp.etsi.org/EDSupdate/List File.asp> 'retrieved on 2004-03-12! | 1,9,16                |
| A          | 9 Protection process, pages 80-91; Annex L (normative): Generic specification of linear protection switching operation, pages 132-141  | 2-8, 10-15            |
|            | ---  | -/--                  |



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

17 March 2004

Date of mailing of the international search report

26/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Carballo da Costa, E

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 03/08633

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No. |
|----------|---|-----------------------|
| Y        | EP 1 014 611 A (CIT ALCATEL)<br>28 June 2000 (2000-06-28)<br>abstract   | 1, 9, 16              |
| A        | column 1, line 1 -column 7, line 46<br>column 9, line 28 -column 11, line 3   | 2-8,<br>10-15         |
| A        | -----<br>MIYAZAKI T ET AL: "A DEMONSTRATION OF AN<br>OPTICAL SWITCH CIRCUIT WITH BRIDGE AND<br>SWITCH FUNCTION IN WDM FOUR-FIBER RING<br>NETWORKS"<br>IEICE TRANSACTIONS ON COMMUNICATIONS,<br>INSTITUTE OF ELECTRONICS INFORMATION AND<br>COMM. ENG. TOKYO, JP,<br>vol. E82-B, no. 2,<br>February 1999 (1999-02), pages 326-333,<br>XP000940183<br>ISSN: 0916-8516<br>the whole document | 1-16                  |
| A        | -----<br>US 2002/150042 A1 (LE GALL LOIC ET AL)<br>17 October 2002 (2002-10-17)<br>page 1, paragraph 5 - paragraph 25<br>page 3, paragraph 40 - paragraph 46  | 1-16                  |
| A        | -----<br>EP 1 280 374 A (CIT ALCATEL)<br>29 January 2003 (2003-01-29)<br>column 2, line 31 -column 3, line 34<br>column 4, line 54 -column 5, line 16<br>column 6, line 37 - line 43<br>column 7, line 47 -column 8, line 1<br>column 9, line 33 -column 11, line 5<br>figure 6   | 1-16                  |



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/08633

| Patent document<br>cited in search report |    | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|---|----|---------------------|----------------------------|---------------------|
| EP 1014611                                | A  | 28-06-2000          | IT MI982791 A1             | 23-06-2000          |
|   |    |                     | EP 1014611 A2              | 28-06-2000          |
|   |    |                     | JP 2000196524 A            | 14-07-2000          |
| US 2002150042                             | A1 | 17-10-2002          | FR 2810746 A1              | 28-12-2001          |
|   |    |                     | EP 1168695 A1              | 02-01-2002          |
|   |    |                     | WO 0199319 A1              | 27-12-2001          |
|   |    |                     | JP 2004501567 T            | 15-01-2004          |
| EP 1280374                                | A  | 29-01-2003          | EP 1280374 A1              | 29-01-2003          |
|   |    |                     | CN 1400781 A               | 05-03-2003          |
|   |    |                     | US 2003041208 A1           | 27-02-2003          |

CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number  
**WO 2005/015795 A1**

- (51) International Patent Classification<sup>7</sup>: **H04J 3/08**
- (21) International Application Number:  
PCT/EP2003/008633
- (22) International Filing Date: 5 August 2003 (05.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **TELECOM ITALIA S.P.A.** [IT/IT]; Piazza degli Affari, 2, I-20123 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **ALLASIA, Andrea** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). **RITA, Roberto** [IT/IT]; Telecom Italia S.p.A., Via di Val Cannuta, 250, I-00100 Roma (IT). **SERRA, Laura** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). **VARETTO, Luigi, Giuseppe** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT).
- (74) Agents: **BATTIPEDE, Francesco et al.**; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milano (IT).


- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,

[Continued on next page]

(54) Title: METHOD FOR PROVIDING EXTRA-TRAFFIC PATHS WITH CONNECTION PROTECTION IN A COMMUNICATION NETWORK, RELATED NETWORK AND COMPUTER PROGRAM PRODUCT THEREFOR



(57) Abstract: Extra traffic (ET) paths are provided in a communication network including at least two protection channels associated to respective transmission channels. Each protection channel admits: - an active state for carrying, in the presence of a failure in said associated transmission channel, traffic to be carried by the associated transmission channel, and - a stand-by state, wherein the protection channel is adapted to carry extra traffic. The protection channels are run in a sub-network connection protection scheme, whereby one of the protection channels in its stand-by state is adapted to ensure recovery of extra traffic carried by the other protection channel while the other protection channel is switched to its active state or is subject to failure.

WO 2005/015795 A1



RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

(48) Date of publication of this corrected version:

30 March 2006

(15) Information about Correction:

see PCT Gazette No. 13/2006 of 30 March 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.